Features & Specification



chilltap



Chilled Water Taps







CH1100 - Brushed Product Code: HC1100-BR

- · Instant filtered chilled water.
- · Gentle touch, lever dispenser
- Spring loaded return mechanism
- Elegant swivelling spout. Tap insulated from heat.
- Tap mounted on either the kitchen work surface or sink.
 (35mm-38mm hole required in bench)
- Reduce chlorine, lead, and other unpleasant tastes, chemicals and odours from the water.
- · Easy to install 5 litre NeoChiller
- Tank plug directly into electrical sockets close to appliance.
- 3-Year Warranty.





NeoChiller, fliters & full installation kit included.




Please note these products are for domestic use only and the warranty is void if installed in a commercial application.


NeoChiller® Specifications






- · Small, compact domestic chiller unit
- · Designed for easy installation under the kitchen sink
- $\cdot\,\,$ Dispenses up to 7 litres per hour of cold, still water between 3°C and 10°C
- · Filtered to remove impurities and odours, without affecting the waters natural mineral content
- \cdot lce-bank cooling technology for optimum performance
- · Standard 3-pin plug that plugs straight into a wall socket.
- · CE approved





Placement guide with minimum clearances for NeoTank installation.

It is recommended to have cabinetry vented to create adequate air-flow.



IMPORTANT NOTICE

Remove red pug from ICE BANK FILL port (C). Connect plastic tube to this port an the other end to the Y fitting (smaller side). Turn on water supply and fill ice bank use fill marking. When full remove plastic tube from chiller and insert plug.

